

ZPMV2.E208099 - Wiring, Printed - Component

Wiring, Printed - Component

AKA PCB D O O

Rozna Dolina 54
Lesce, 4248 Slovenia

E208099

Type	Cond Width		Max				Assembly			Max		Meets C		
	Min	Min	Cond	SS/	Area	Solder	Solder	Oper	Temp	Flame	UL796	T		
	mm(in)	mm(in)	Thk	DS/	Diam	Limits	Process (IPC)	Temp	Class	UL796	DSR	I		
Single layer printed wiring boards														
1	0.15 (0.006)	0.23 (0.009)	33 (1.3)	SS	20.6 (0.8)	260	10	-	-	105	V-0	All	0	
3	0.18 (0.007)	0.25 (0.01)	33 (1.3)	SS	20.6 (0.8)	270	10	-	-	130	V-0	All	*	
Single Sided Metal Based Printed wiring boards														
4	0.10 (0.004)	0.10 (0.004)	35 (1.38)	SS	30.0 (1.2)	260	10	-	-	130	V-0	All	0	

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or trademark



type designation. May be followed by a suffix to denote factory identification

or burning test classification.

Last Updated on 2021-06-10

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

ZPMV8.E208099 - Wiring, Printed Certified for Canada - Component

Wiring, Printed Certified for Canada - Component

AKA PCB D O O

Rozna Dolina 54
Lesce, 4248 Slovenia

E208099

Type	Cond Width		Max					Assembly		Max		Meets C	
	Min	Min	Cond	SS/	Area	Solder	Solder	Oper	Flame	UL796	T	DSR	I
	mm(in)	mm(in)	Thk	DS/	Diam	Limits	Process (IPC)	Temp	Class	UL796			
Single layer printed wiring boards													
1	0.15 (0.006)	0.23 (0.009)	33 (1.3)	SS	20.6 (0.8)	260	10	-	-	105	V-0	All	0
3	0.18 (0.007)	0.25 (0.01)	33 (1.3)	SS	20.6 (0.8)	270	10	-	-	130	V-0	All	*
Single Sided Metal Based Printed wiring boards													
4	0.10 (0.004)	0.10 (0.004)	35 (1.38)	SS	30.0 (1.2)	260	10	-	-	130	V-0	All	0

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or trademark  type designation and the Recognized Component Mark for Canada,



. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2021-06-10

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"